

Distributed by Step Global **Ph**: +61 3 9551 7334 **Email**: sales@stepglobal.com www.shop.stepglobal.com

LOW PROFILE HEAVY DUTY WIFI ANTENNA

HD4-2400

PRODUCT OVERVIEW

The HD4-2400 is a heavy-duty WiFi antenna for fixed M2M and mobile applications. This omni-directional antenna operates in the frequency range of 2400-2485 MHz, with a peak gain of 4 dBi. It is a low-profile solution for environments that are subject to physical wear and tear. Impact from a car tire passing overhead or damage caused by an animal in an agriculture setting are examples of durability tests this antenna handles.

This heavy-duty WiFi antenna is enclosed in a durable overmolded radome for weather protection and impact resistance. It is ground plane independent, therefore no ground plane is required for proper operation. It has a 57-degree vertical beamwidth and a 360 degree horizontal beamwidth, giving this product effective capability for omni-directional WiFi coverage.

Visit our eStore to customize an Antenna online.

	Electrical Specifications						
Frequency & Gain	2400 - 2485 MHz, 4 dBi Peak Gain						
Bandwidth	Horizontal Beamwidth (Azimuth)	360°					
	Vertical Beamwidth (Elevation)	57°					
Electrical Uptilt	30° Max on Ground Plane						
Polarization	Vertical						
VSWR	2:1 Max						
Impedance	50 Ohm Nominal						
Power Rating	10 Watts						
Mechanical Specifications							
Radome Material & Color	Black UV Stable Polyamide, Available in Black						
Radome Dimension	2.75" (70 mm) in Diameter & 0.60" (15 mm) in Height						
Net Weight	8 oz (0.5 lbs) (226 g)						
Standard Connector	SMA Plug (Male), Other Connectors Available Upon Request						
Standard Cable	3 FT (914 mm) of LL-195, Other Cable Lengths Available Upon Request						
Mounting	5/8"-24 x 0.50" (16 mm Diameter x 12mm Thick) Threaded Stud						
Operating Temperature	-40° to +80° C						
Storage Temperature	-40° to +90° C						
Shock and Vibration	EN 61373, IEEE1478, MIL-810G						
Weather Proof	IP67 (When Properly Mounted)						
RoHS Compliant	Yes						





Н	D	2	-	2	4	0	0	-	3	C	-	В	L	К	-	3	6
Approx. Frequency WiFi Cable/Connector ————————————————————————————————————																	
Color-																	
Cable Length (in inches)												I					

HIGHLIGHTS:

- Low-Profile WiFi Coverage 2.4 GHz
- Ground Plane Independent
- Overmolded for Weather & Impact Resistance
- High Performance; High Gain
- Made-in-the-USA & UK

RELATED MODELS:

- SMD-W-2 (2x MIMO WiFi 2.4 & 5 GHz)
- SMD-W-3 (3xMIMO WiFi 2.4 & 5 GHz)
- RM3-2400 (RM Series, Same Freq)
- NXD-W (4x WiFi at 2.4 & 5 GHz)
- MRM3-2400/5500 (2.4 & 5 GHz)

COMMON APPLICATIONS:

- Precision Agriculture
- WiFi Networks & Hotspots
- Industrial IoT



US Headquarters +1.847.671.6690 • US/CA Toll Free +1.800.648.2800 European Facility +44.1543.459555 • **www.MobileMark.com**