



SMW-412 multiband, 4-cable LTE 700 MHz, AWS, WiFi & GPS

- 4 antennas in 1 antenna housing
- Covers GPS, 700 MHz LTE, AWS, WiFi, & Public Safety 4.9 GHz
- Saves time and money by reducing the number of installations
- Available in either Surface-mount (SMW Series or Mag-mount (MGW Series)

The SMW-412 Series Antennas features 4 elements in one antenna radome. The unique feature of this model is that the cellular element (Cable 1) is extremely widebanded and can cover: LTE at 700 MHz as well as the established 850/1900 GSM/CDMA bands, 1.7/2.1 AWS bands and WiMAX 2.5 all on a single board.

This antenna is truly ready for any 4G rollout but is also compatible with earlier generation such as GPRS. See the spec table below for exact frequencies covered on each cable.

In addition to covering all of the cellular bands on Cable 1, the antenna also covers 2.4/5 dual-band WiFi on Cables 2 & 3. Other specialized applications are possible, e.g. Public Safety coverage at 700 MHz & 4.9 GHz, Military at 4.4 GHz or DSRC at 5.9 GHz.

The antenna is enclosed in a 4.2"D x 3.2"H (107 mm x 81 mm) weatherproof radome, and supplied with all mounting hardware and a sealing gasket.

The radome is available in either black or white. The antennas are available in either surface mount or mag-mount models. The antennas can also be configured for combined GPS & Glonass use.

Model Configurator

SMW-412- - -

Cable/Connector 1

Cable/Connector 2

Cable/Connector 3

Cable/Connector 4

Color

Cable Length in Inches (eg. 12 or 180)

Example: SMW-412-3C3C3C2C-WHT-180
MGW-412-3C3C3C2C-BLK-180

Specify "SMWG" or "MGWG" instead of "SMW" or "MGW"
for GPS/Glonass combination antenna.

Cable Options:		Connector Options:		Color Options:	
Code	Cable	Code	Connector	Code	Color
1	RG-58	A	TNC	WHT	White
2	RG-174	B	Mini UHF	BLK	Black
3	RF-195	C	SMA		
		D	SMB		
		E	MCX		

(Other Configurations available.)

Specifications			
Frequency & Gain*:	Cable 1	694-894 MHz, 3 dBi & 1.7-2.7 GHz, 5 dBi	Cable:
Cable 2	Cable 3	2.4-2.5 & 4.9-6.0 GHz, 5 dBi	Cables 1 - 3
Cable 4 (GPS)	Cable 4 (GPS)	2.1-2.5 & 4.4-6.0 GHz, 5 dBi	Cable 4
VSWR*:	VSWR*:	1575.42 +/- 2 MHz, LNA: 26dB	Connector:
Nominal Impedance:	Nominal Impedance:	5 dBi nominal RHCP	Case Material:
Maximum Power:	Maximum Power:	2:1 max over range	MGW Mounting:
GPS Amplifier Bias:	GPS Amplifier Bias:	50 ohms	SMW Mounting:
GPS Noise Figure:	GPS Noise Figure:	10 Watts	Operating Temp:
GPS Current:	GPS Current:	2.7 to 5 VDC	Shock & Vibration:
GPS & Glonass Option:	GPS & Glonass Option:	2.0 dB max, 1.7 dB typical	Dust/Water Ingress:
Case:	Case:	20 mA max, 10 mA typical	IP67
		1575 MHz & 1612 MHz	*Measured on 1' ground with 1' cable
		4.2"D x 3.2"H (107 mm x 81 mm)	
		add 1/2" (13 mm) for mag base	