

Additional accessories

Designation	Transmission speed	Wavelength	Fiber optic cable type	Distance	Insert type	Connector type	Operating temperature	Notes
BTP-3124-L2TD	1.25 Gbps	1310 nm	MM/SM	2/20 km	SFP	LC	-40~85°C	100 Mbps support
BTP-3124-L4TD	1.25 Gbps	1310 nm	SM	40 km	SFP	LC	-40~85°C	100 Mbps support
BTP-3103-L2TD	155 Mbps	1310 nm	MM/SM	2/20 km	SFP	LC	-40~85°C	---
BTP-3103-L4TD	155 Mbps	1310 nm	SM	40 km	SFP	LC	-40~85°C	---

List of proposed power supplies for BITSTREAM devices

Designation of the power supply	Output voltage range	Nominal output power	Number of ports with PoE (15W)	Number of ports with PoE+ (30W)	Number of ports with PoE++ (60W)	Number of ports with PoE++ (90W)	Operating temperature C-standard T-industrial	Notes
	DC							
ZAS-24-20-R-T	24 V	20 W	0	0	0	0	-20°C ~ +70°C	No PoE support
ZAS-48V56-40-R-T	48 - 56 V	40 W	2	1	0	0	-20°C ~ +70°C	PoE support